

Novo enrolador de cabo com **2 USB**

Ref. 7321USB



2 USB: 5V=, 2,4A; Total 12W

Gancho retrátil

Furos de fixação de parede

Disjuntor térmico

3 bases Schuko



Máx. estendido: 3200W
Máx. enrolado: 1100W

5m de cabo H05VV-F 3G1,5 mm²



Enroladores de cabos destaque:



Ref.	Descrição		
 			
1 Base 2P+T, 16A 250 V~. Cabo H05VV-F. Com suporte para fixação à parede.			
71231A	Cabo 11 m (9+2). 3G1.5.	1	4
71251A	Cabo 16 m (14+2). 3G1.5.	1	2



3 tomadas 2P+T, 16A 250V~.+ 2 USB: 5V=, 2,4A; Total 12W Cabo H05VV-F.			
7321USB	Cabo 5m. 3G1.5. Pot. máx.: 3.200 W / 1.100 W	1	6



4 tomadas 2P+T, 16A 250V~. Cabo H05VV-F. Máx 3,500W.			
7413/2	Cabo 15m. 3G1.5.	1	4



4 tomadas 2P+T, 16A 250V~. Cabo H05VV-F. Máx 3,500W.			
7423/2	Cabo 15m. 3G1.5.	1	2



4 tomadas 2P+T, 16A 250V~. Cabo H05VV-F. Máx 3,500W.			
7425/2	Cabo 25m. 3G1.5.	1	2
7427/2	Cabo 50m. 3G1.5.	1	2



4 tomadas 2P+T, 16A 250V~. Com tampa Máx 3,500W.			
7425/1T	Cabo 25m. 3G1.5. H05VV-F	1	2
7425/1TG	Cabo 25m. 3G1.5. H07RN-F.	1	2
7427/1T	Cabo 50m. 3G1.5. H05VV-F	1	2
7427/1TG	Cabo 50m. 3G1.5. H07RN-F.	1	2



1 Base móvel 2P+T, 16 A/250 V~.. Cabo H05VV-F. Máx 3,500W. De jardim			
7125TT	Cabo 25m. 3G1.5.	1	2
7127TT	Cabo 50m. 3G1.5.	1	2



Suporte de parede para enroladores de cabos.			
SOP-7000	Preto.	4	95



4 tomadas. Sem Cabo. Máx 3,500W.			
TB7427/3	Cabo 60m para 3G1.5 e 30m para 3G2.5.	1	---

Se você deseja conhecer toda a gama de produtos, faça a leitura deste código:



Solera[®]

Portalámparas y Accesorios Solera S.A. - C/ Villa de Madrid, 53
46988 Paterna (Valencia) España-Spain
solera@psolera.com - export@psolera.com

www.psolera.com

