

Industrial flush interlocked socket 3P+E, 32A 400V~. IP44

Industrial flush interlocked socket 3P+E, 32A 400V~. IP44
Common applications: Industrial environments (factories, warehouses, etc.)



Features

Type	Base interbloqueante traspunto
No. of poles	3P + T
Type of terminal connection	Screw connection
Earth position	6h
Interlocking	Yes
Frame for Indubox	MR1300X
Nominal current	32A
Nominal voltage	400V
Color	Red

Technical data

Protection Degree (IP)	IP44
Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Dimensional stability	-25 °C -> +80 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2001;UNE-EN 60309-2:2001
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220043350
EAN code container	8423220043350
EAN code packaging	18423220043357
Units packaging	0
Units carton	1
Pallet Units	99999
Packaging Measures cm	19,5x11x14
Packaging Weight (Kg)	0,72
Tariff code	85366990

Sketch



Ampere	16			32		
Pole	3	4	5	3	4	5
a	58	60	61	66	66	67

