

Mobile industrial plug 2P+E, 63A 230V~. IP67

Mobile industrial plug 2P+E, 63A 230V~. IP67
Common applications: Industrial environments (factories, warehouses, etc.)



Features

With contact pilot	Yes
Type	Mobile industrial plug
No. of poles	2P + T
Type of terminal connection	Screw connection
Earth position	6h
Nominal current	63A
Nominal voltage	230V
Color	Blue

Technical data

Protection Degree (IP)	IP67
Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Installation temperature	-25 °C -> +60 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2001;UNE-EN 60309-2:2001
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes



Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220042650
EAN code container	8423220042650
EAN code packaging	18423220042657
Units packaging	1
Units carton	2
Pallet Units	99999
Packaging Measures cm	28,5x13,5x19
Unit weight (g)	582
Container Weight (Kg)	0,58
Packaging Weight (Kg)	1,30
Tariff code	85366990

Sketch



Ampere	63		
Pole	3	4	5
a[mm]	250	250	250
b [mm]	102	102	102
c [mm]	184	184	184
K [mm]	14,5-36	14,5-36	14,5-36
SW [mm]	61	61	61

