935144

Industrial surface plug 3P+E, 32A 400V~. IP44

Industrial surface plug 3P+E, 32A 400V~. IP44
Common applications: Industrial environments (factories, warehouses, etc.)

Features

Type	Surface Flush plugs
No. of poles	3P + T
Type of terminal connection	Screw connection
Earth position	6h
Nominal current	32A
Nominal voltage	400V
Color	Red

Technical data

Protection Degree (IP)	IP44
Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 ºC
Heat resistance (Ball pressure)	125 ºC
Dimensional stability	-25 ºC -> +80 ºC
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2001;UNE-EN 60309-2:2001
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220046450
EAN code container	8423220046450
EAN code packaging	18423220046457
Units packaging	1
Units carton	10
Pallet Units	99999
Packaging Measures cm	29x23x19
Unit weight (g)	233
Container Weight (Kg)	0,23
Packaging Weight (Kg)	2,50
Tariff code	85366990

Sketch



Ampere	16				32			
Pole	3	4	5	7	3	4	5	7
a [mm]	120	121	122	122	131	131	132	132
b [mm]	76	76	79	79	82	82	85	85
M [mm]	25	25	25	25	25	25	25	25