

Metal frame and door for 304 x 414 mm construction hole.

Metal frame and door for 304 x 414 mm construction hole. IK07. White colour. Matte finish and epoxy treatment. Optional key ref. CER-MP28. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
Dimensions outside (mm) (width x height x depth)	362x462
Dimensions inside (mm) (Width x Height x Depth)	304x414x27
Frame and door material	Metallic
Door color	White
Door opening	Horizontal
Door closing system	Handle
Reversible door	Yes
Possibility of mounting with key / padlock	Key

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK07
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWT)	650°C

Heat resistance (Ball pressure)	70°C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208: 2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220073517
EAN code container	8423220073517
EAN code packaging	18423220073514
Units Container	1
Units Packaging	3
Pallet Units	240
Packaging Measures cm	59,5x49x37,5
Container Weight (Kg)	0,01
Packaging Weight (Kg)	1,01
Tariff code	85366990