

Network termination box. Flush for hollow wall
Empty box. Flush dimensions 688 x 526 x 86 mm.

Network termination box. Flush in hollow wall . Empty box. Flush dimensions 688 x 526 x 86 mmWith frame and door with heat dissipation grid. Linkable horizontally and vertically. With Ø 50 mm tubes for connection between boxes. With internal partition. Fixing system using m ulti-perforated support for hollow wall black colour. With key.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	IT boxes
Installation method	For hollow wall.
Use	Domestic / Tertiary
Location type	Inside
Dimensions outside (mm) (width x height x depth)	730x544x113
Dimensions gap (mm) (Width x Height x Depth)	688x526x86
Case material	Insulation
Frame and door material	Insulation
Case color	Blue
Door color	White with heat dissipation grid.
Door opening	Horizontal
Battens included	No
Ticket type	Unfathomable
Linkable	Vertically and horizontally
Lid closure system	Metal screw
Door closing system	A Pressure
Reversible door	Yes

Possibility of mounting strips	Yes (not included)
Possibility of putting lock	Key included
Fixing system to the hollow partition.	Multi-perforated support for hollow wall black colour.

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK08
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Work stress	400 Vac
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-22:2007 UNE-EN 62208:2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220261013
EAN code container	8423220261013
Units packaging	1
Units carton	1
Pallet Units	35
Tariff code	39259010

Sketch



Documentation and downloads



[Assembly instructions \(4.37MB\)](#)



[Commercial doc. \(3.42MB\)](#)



[Commercial doc. \(0.51MB\)](#)