
KIT-MRP14NG

Metal frame and door for 304 x 279 mm construction hole. Graphite Colour



Metal frame and door for 304 x 279 mm construction hole.IK07. Graphite colour. Optional key ref. CER-MP28.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Features

Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
Dimensions outside (mm) (width x height x depth)	362x327
Dimensions inside (mm) (Width x Height x Depth)	304x279x27
Frame and door material	Metallic
Door color	Graphite
Door opening	Horizontal
Door closing system	Handle
Reversible door	Yes
Possibility of putting lock	Key

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK07
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220246508
EAN code container	8423220246508
EAN code packaging	18423220246505
Units packaging	1
Units carton	3
Pallet Units	240
Tariff code	85366990

Documentation and downloads

Series replenishments (0.06MB)

Series replenishments (0.1MB)