Connection sealed box without cones. Grey colour. External dimensions 270x500x140 mm Internal dimensions 263 x 493 x 129 mm



Connection sealed box without cones. Grey colour. With centricity points. IP65. IK08. External dimensions 270x500x140 mm Interior dimensions 263 x 493 x 129 mm. Quick closure with stainless screws.
Common applications: Industrial environments (factories, warehouses, etc.)

Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	270x500x140
Dimensions inside (mm) (Width x Height x Depth)	263x493x129
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Battens included	No
Ticket type	With centricity points.
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Possibility of mounting strips	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (not included)

Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	650 ºC
Heat resistance (Ball pressure)	70 ºC
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability


According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220048089
EAN code container	8423220048089

EAN code packaging	18423220048086
Units packaging	1
Units carton	6
Pallet Units	72
Packaging Measures cm	59,5x51x42,5
Unit weight (g)	1942
Container Weight (Kg)	1,95
Packaging Weight (Kg)	12,92
Tariff code	85381000

Sketch



Documentation and downloads

Assembly instructions (2.01MB)

Series replenishments (0.05MB)

Industrial cabinets IP65, IK08 (Solera) (Ed. 2024)