

LED dimmer. Monobloc. Flush.

LED dimmer. Monobloc. Flush.White colour. Dimensions 83 x 81 mm. Screw connection.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	Regulator
Type of installation	Flush
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Type of operation	Rotary
Power	3-250 W
Dimensions	83 x 81
With fixing claws	Yes
Monobloc (with frame included)	Yes
Frame color	White

Technical data

Protection Degree (IP)	IP40
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-2-1:2005
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220098848
EAN code container	8423220098855
EAN code packaging	18423220098852
Units packaging	10
Units carton	120
Pallet Units	4320
Packaging Measurements cm	26x10x14
Packaging Measures cm	44x40x27,5
Unit weight (g)	18
Container Weight (Kg)	0,33
Packaging Weight (Kg)	4,71
Tariff code	85366990

Documentation and downloads

 [Commercial doc. \(20.04MB\)](#)

 [Mechanism scheme table \(0.91MB\)](#)

 [Flush switches of Eruopa range \(Solera\)](#)

 [Assembly flush switches form Europa range \(Solera\)](#)