

Socket 2P+E, 16A 250V + 1 USB A+ 1 USB C. 2,1A 5V.
Flush

Socket 2P+E, 16A 250V ~ + 1USB type A & 1 USB type C 2.1A 5V. Screw connection. White colour. Flush. Dimensions 83x81 mm. With shutter. Without frame

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	Fixed base + USB
Type of installation	Flush
Rated current	16A - 2,1Adc
Nominal voltage	250V~ (50/60 Hz) - 5Vdc
Connection type	Fast connection
Dimensions	83 x 81
With fixing claws	Yes

Technical data

Protection Degree (IP)	IP40
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
According to REBT	Yes

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220247505
EAN code container	8423220247499
EAN code packaging	18423220247496
Units packaging	10
Units carton	120
Pallet Units	4320
Tariff code	85366990

Documentation and downloads

 [Assembly instructions \(0.58MB\)](#)

 [Mechanism scheme table \(0.91MB\)](#)

 [Assembly flush switches form Europa range \(Solera\)](#)

 [Commercial doc. \(20.04MB\)](#)

 [Flush switches of Eruopa range \(Solera\)](#)