

2 pole switch 10AX 250V ~ . IP54. Surface.

2 pole switch. 10AX 250V ~ . IP54. Surface. Tube inputs up to Ø 20 mm. External dimensions 65 x 80 x 55 mm. Screw connection.
Common applications: Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)



Features

Mechanism type	Bipolar switch
Type of installation	Surface
Rated current	10AX
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Tube inlet	Up to Ø 20 mm
Flexible cable section	Up to 2.5 mm²
Rigid cable section	Up to 2.5 mm²
Type of operation	Rocker key
Dimensions	65 x 80 x 55
Monobloc (with frame included)	Yes
Frame color	Grey

Technical data

Protection Degree (IP)	IP54
Insulation class	Class II
Fire resistance (GWEPT)	650/850 °C
Heat resistance (Ball pressure)	70/125 °C
Installation temperature	-5 °C -> +60 °C

Free of halogens	Yes
------------------	-----

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1:2018
According to REBT	Yes
VDE certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220086869
EAN code container	8423220086876
EAN code packaging	18423220086873
Units packaging	20
Units carton	100
Pallet Units	3000
Packaging Measurements cm	33,5x12x19,5
Packaging Measures cm	61,5x22x34,5
Unit weight (g)	112
Container Weight (Kg)	2,35
Packaging Weight (Kg)	12,31
Tariff code	85366990

Documentation and downloads

- | | | | |
|--|---|---|--|
|  | Assembly instructions (0.58MB) |  | Commercial doc. (2.27MB) |
|  | Mechanism scheme table (0.47MB) |  | Watertight switch IP54/44 (Solera) |
|  | Assembly watertight switches IP54/44 (Solera) | | |