

Description and characteristics

- Reeled extension with side earth lug.
- Complies with the norm UNE EN 61242
- With shutter.
- With power limiter.

References



(Example)

REF	SOCKETS	PLUG	Cable y Section	MAX. Power	IP	Cable Length
73362	3 x 2P+E 16A 250 V	1 x 2P+E 16A 250V	H05VVF 3G2,5	3.680 W.	IP 44	30
72353	2 x 3P+E 16A 400V	1 x 3P+E 16A 400V	H05VVF 4G2.5	4.800 W.	IP 44	25
7400TT	4 x 2P + E 16A 250V			3.680 W.		
71344	1 x 3P+N+E 16A 250V	1 x 3P+N+E 16A 250V	H05VVF 5G2.5	4.800 W.	IP 44	20
71353	1 x 3P+N+E 16A 250V	1 x 3P+N+E 16A 250V	H05VVF 4G2.5	4.800 W.	IP 44	50
71362	1 x 3P+E 16A 400V	1 x 3P+E 16A 400V	H05VVF 4G2.5	4.800 W.	IP 44	25
73344	1 x 2P+E 16A 250 V	1 x 3P+N+E 16A 250V	H05VVF 5G2.5	4.800 W.	IP 44	20
71361		1 x 2P+E 16A 250 V	H07RNF 3G2.5	3.680 W.	IP 44	30
75562	1 x 2P+E 16A 250 V	1 x 2P+E 16A 250 V	H07RNF 3G2.5	3.680 W.	IP 67	30
75553	1 x 3P+N+E 16A 250V	1 x 3P+N+E 16A 250V	H07RNF 4G2.5	4.800 W.	IP 67	25
75544	1 x 2P+E 16A 250 V	1 x 3P+N+E 16A 250V	H07RNF 5G2.5	4.800 W.	IP 67	20

Specifications

- Directive 2014/35/UE
- Low Voltage Electrotechnical Regulation
- Norm UNE 21031 (HD21.1S3)
- Norm EN 61242
- Norm UNE 20315

Technical Data

- Fire Resistance 650°C - 750°C (Ensayo del Hilo Incandescente).
- Heat Resistance 70°C -125°C (Ensayo de presión a la bola).
- HALOGEN FREE Material.

