

**Description**

- Junction boxes for flush fit installation
- Installation can be in solid walls or ceilings.
- Halogen free material.
- Screw closing lid.
- White lids.



**Dimensions and characteristics**

REF	INTERNAL DIMENSIONS (mm)			Entries	Ø (mm)	ADICIONAL INFORMATION
	Length	Height	Depth			
277	430	147	65	30	32	ADICIONAL PLASTIC GRIP
314	200	130	60	20	32	ADICIONAL PLASTIC GRIP
320	200	200	65	16	40	
323	150	150	50	12	32	
324	250	250	60	20	40	
361	100	50	45	6	32	
362	100	100	45	12	25	
363	160	100	50	16	25	
635	67	67	42	5	25	ADICIONAL PLASTIC GRIP. ROUND LID
5501	100	170	40	16	32	
5502	200	300	60	20	40	1 ADDICIONA SEPARATING WALL (2 COMPARTMENTS)

REF	INTERNAL DIMENSIONS (mm)			Entries	Ø (mm)	ADICIONAL INFORMATION
	Length	Height	Depth			
5503	300	500	85	50	40	2 SEPARATING WALLS (3 COMPARTMENTS)
5506	300	500	60	50	40	
5520	200	160	70	18	40	WITH SEPARATING WALLS
5530	300	160	70	14 10	32 40	ADICIONAL PLASTIC GRIP. ROUND LID
5540	400	160	70	30	40	
5550	500	160	70	12 18	40 50	
6635	65	65	40	9	25	ADICIONAL PLASTIC GRIP. ROUND LID
575	Ø 65		40	5	25	ROUND BOX AND LID
414	Ø 80		40	8	25	

**Technical information**

- Directive 2014/35/UE
- Regulation EN 60 670-1
- Fire resistance (Glow Wire Test 650°C)
- Heat resistance (Ball pressure tested at 70°C)
- Dimensional stability -5°C to +60°C
- Halogen free material



ED02/ July 2016