

Description y characteristics

- Trunking
- IP40
- Wrap around
- Thermoplastic material
- HALOGEN FREE material
- Conduit length : 2 m.

References

REF	DESCRIPTION	FIXING	DIMMENSIONS	COLOR	MATERIAL
9154070	Trunking complet	Screw	40x70 mm	White	PVC
9154070 T	Cap	Screw		White	PVC
9154070 B	Base	Screw		White	PVC
9156060	Trunking complet	Screw	60x60 mm	White	PVC
9156060 T	Cap	Screw		White	PVC
9156060 B	Base	Screw		White	PVC
91560100	Trunking complet	Screw	60x100 mm	White	PVC
91560100 T	Cap	Screw		White	PVC
91560100 B	Base	Screw		White	PVC



Specifications

- EN 50085-1
- Directive 2011/65/UE (RoHS)

Technical Data

- Fire resistance 850°C (Glow Wire Temperature)
- HALOGEN FREE material
- IP40



Description y characteristics

- Mini trunking
- IP40
- Wrap around
- Thermoplastic material
- HALOGEN FREE material
- Conduit length : 2 m.

References

REF	FIXING SYSTEM	DIMMENSIONS	COLOR	MATERIAL
9160712	Autoadhesive	7 x 12 mm	White	PVC
9161016	Autoadhesive	10 x 16 mm	White	PVC
9161020	Autoadhesive	10 x 20 mm	White	PVC
9161212	Autoadhesive	12 x 12 mm	White	PVC
9161616	Autoadhesive	16 x 16 mm	White	PVC
9161625	Autoadhesive	16 x 25 mm	White	PVC
9162525	Autoadhesive	25 x 25 mm	White	PVC
9162540	Autoadhesive	25 x 40 mm	White	PVC



Specifications

- EN 50085-1
- Directive 2002/95/UE (RoHS)

Technical Data

- Fire resistance 850°C (Glow Wire Temperature)
- HALOGEN FREE material
- IP40



Description y characteristics

- Mini Trunking
- IP40
- Wrap around
- Thermoplastic material
- HALOGEN FREE material
- Conduit length : 2 m.

References

REF	FIXING SYSTEM	DIMMENSIONS	COLOUR	MATERIAL
9150712	Screw	7 x 12 mm	White	PVC
9151016	Screw	10 x 16 mm	White	PVC
9151020	Screw	10 x 20 mm	White	PVC
9151212	Screw	12 x 12 mm	White	PVC
9151616	Screw	16 x 16 mm	White	PVC
9151625	Screw	16 x 25 mm	White	PVC
9152525	Screw	25 x 25 mm	White	PVC
9152540	Screw	25 x 40 mm	White	PVC
9154040	Screw	40 x 40 mm	White	PVC



Specifications

- EN 50085-1
- Directive 2002/95/UE (RoHS)

Technical Data

- Fire resistance 850°C (Glow Wire Temperature)
- HALOGEN FREE material
- IP40

